

HEMERA

Specifications Sheet



Ordering Information ¹						
Model	Length	Power ²	Color Temp.	Optics	Voltage	Installation Options
HM					24	
HM	320 620 920 1070 1220	H L	27 30 40 27 30 40	SP	24	S A EA

¹ Specify remote power supply separately below.

Surface mounted linear LED with high performance optics for outdoor and indoor use. Continuous run of standard lengths up to 10m plug and play.
Surface or adjustable bracket installation.
IP67 rated

Luminaire

- Continuous run of standard lengths up to 10m plug and play
- High performance silicone optics
- UL STD 1598, IP67
- Remote power supply
- Extruded aluminum body, RAL9003
- Protective tempered glass cover
- Installation clips, adjustable holder
- IP67 connector (plug and play)
- Cross section 27mm (1.06") (W), 37.2mm (1.46") (H)
- Supplied with plug and play IP67 oil and water resistant 0.3m (11.81") feed cable standard

Length

- 320mm (12.6")
- 620mm (24.4")
- 920mm (36.22")
- 1070mm (42.12")
- 1220mm (48.03")

Power²

- H - 23W/m, 2760 lm/m
- L - 10W/m, 1200 lm/m

(delivered lumen output)

Color Temperature

- 27 - 2700K
- 30 - 3000K
- 40 - 4000K
- Binning +/-50k
- CRI: > 85

Optics

- SP - 15° angle

Voltage

- 24 - 24Vdc fixture voltage

Installation Options

- S - surface
- A - adjustable bracket
- EA - extended adjustable bracket

Cable options

Jumper Cable


- 201795 - L= 0,3m
- 201741 - L= 1m

Lead Cable

- 201734 - L= 1m

(must be specified)

320mm / 620mm / 920mm / 1070mm / 1220mm
(12.6" / 24.4" / 36.22" / 42.12" / 48.03")



Power Supply¹

On/Off

- 101074 - OT80 24V P
- 101278 - OT120 24V P
- 101043 - OT240 24V P

Power Supply integrated controls

- 100721 - OT80 24V DIM P (1-10V)

- 100720 - OT120 24V DIM P (1-10V)
- 101093 - OT240 24V DIM P (1-10V)

Controls

- 101046 - OT DIM 1/10V 120W
- 101047 - OT1 DALI DIM 120W