



Arpool Iris Efecta

Specification Sheet



UL STD 676 swimming pool rated
CSA C22.2#89 swimming pool rated
IP68

LUMINAIRE FEATURES

Design and Application

- Installation depth max. up to 3m (10')
- Recommended installation depth
0,3m-0,6m (1'-2')
- Max tile thickness 25mm (1")
- Trim flange overlap 10mm (0,4")
- DMX, DALI, 0-10V compatible (remote)
- Floor, wall, and stairs installation
- Large and medium pools
- Fountains and water features
- Individual engine rotation 20° all directions
- Horizontal and vertical installation

Performance

- IK10, Tempered glass, crystal clear
- Chlorine and saline environment
- Stainless Steel type 316L, marine grade
- Galvanic current protection
- Thermal fold back technology
- LED Lifetime TM-21 @ 105°C
L80(24K) = 145,000 hours
- Supplied with oil and water resistant
3m (10') feed cable as standard
- CRI: > 85
- 2 Step MacAdam

Safety

- Child safe - no internal access during rotation
- Remote power supply
- Low voltage operation
- Recessed installation

Sustainability


- Recyclable material
- Replaceable engine (page 3)

Installation housing


- FAIE - Iris Efecta

Power supplies

- List of proposed power supplies that are to be ordered separately.
- Click [here](#) for list of available drivers.
- Click [here](#) for voltage drop and distances.



360 ° Rotation,
20° tilt screw adjustment



Iris engine protrusion
min 9mm - max 16mm

Click [here](#) to download fixture installation manual.
Click [here](#) to download housing installation manual.
Click [here](#) to download CAD file.
Click [here](#) to download IES-LTD data.



Arpool Iris Efecta

ORDERING INFORMATION

MODEL

FAIE

APPLICATION

TM

- TM - Ø150mm x H-90mm (Ø5,5" x L-3,5")

POWER

H

- H - 15W 3000/4000K, 1200lm
- H - 15W RGBW

COLOR TEMP.

27

- 27 - 2700K

30

- 30 - 3000K

40

- 40 - 4000K

TW

- TW - Tunable white (2200-4000K)

RGBW

- RGBW (W 4000K)

OPTICS

SP

- SP - Spot - 15°

FL

- FL - Flood - 40°

W

- W - Wide - 70°

VOLTAGE

12

- 12 - 12VDC fixture voltage

24

- 24 - 24VDC fixture voltage

OPTIONS

3

- 3* - standard feed cable 3m (10')

6

- 6 - luminaire supplied with 6m (20') feed cable

9

- 9 - luminaire supplied with 9m (30') feed cable

20

- 20 - luminaire supplied with 20m (65') feed cable

GLARE CONTROL

1


- 1 - Half moon



Arpool Iris Efecta

HOUSING

Installation housing - FAIE * fits 1m (3") cable
Concrete Pool Installation



REPLACEABLE ENGINE

MODEL
FX IE
POWER
H
COLOR TEMP.
30
40
RGBW
OPTICS
SP
FL
W
VOLTAGE
12
24
OPTIONS
X

*Replaceable Iris engine - code for single Iris engine unit to be order separately in the following cases:

- Servicing
- Customization (optical and color variations - excluding RGBW)

Note:
For details on specific depths, tiling thickness and other please refer to both Installation instructions for fixture and housing.