



RDD35 Deco

Specification Sheet



UL STD 1598
IP67

LUMINAIRE FEATURES

Design and Application

- Architectural and landscape lighting
- Small interior lobby spaces
- Recessed floor installation
- Gravel, soil or concrete installation
- UL STD 1598, IP67, Wet location, drive over rated 1500 kg (3300lb)

Performance

- IK10, Tempered glass, crystal clear
- Aluminium construction fixture body
- Stainless steel type 304 flange
- Snap in installation with no exposed hardware
- Galvanic current protection (installation housing)
- Lifetime TM-21 @85C L90(9K)=54400h
- Supplied with oil and water resistant 0.3m (1') feed cable as standard
- CRI: > 85
- 2 Step MacAdam

Safety

- Remote power supply
- Low voltage operation
- Recessed installation

Sustainability

- Recyclable material

Installation housing

- RD35C - Concrete
- RD35T - Tiles


Accessories

- 201090 - Removal tool


Power supplies

- List of proposed power supplies that are to be ordered separately.
- Click [here](#) for list of available drivers.
- Click [here](#) for voltage drop and distances.

Trim (TM)



Trimless (TS)



Click [here](#) to download fixture installation manual.
Click [here](#) to download housing installation manual.
Click [here](#) to download CAD file.
Click [here](#) to download IES-LTD data.



RDD35 Deco

ORDERING INFORMATION

MODEL

FRDD35

INSTALLATION

TM

- Trim (TM)

TS

- Trimless (TS)

POWER

L

- L - 1,2W, 2700 - 3000K - 68 lm

H

- H - 3W, 2700 - 3000K - 186 lm

COLOR TEMP.

27

- 27 - 2700K

30

- 30 - 3000K

OPTICS

SP

- SP - Spot - 17°

FL

- FL - Flood - 41°

GR

- GR - Graze - 13° x 41°

SX

- SX - Spot - 17° + hex

FX

- FX - Flood - 41° + hex

GX

- GX - Graze - 13x41° + hex

VOLTAGE

24

- 24 - 24VDC fixture voltage

OPTIONS

3

- 3 - luminaire supplied with 3m (10') feed cable

6

- 6 - luminaire supplied with 6m (20') feed cable

9

- 9 - luminaire supplied with 9m (30') feed cable

GLARE CONTROL

1


- 1 - with half moon




RDD35 Deco

INSTALLATION DETAILS

Installation housing - RD35C - Concrete installation



Installation housing - RD35T - Tiles installation



Note:
For details on specific depths, tiling thickness and other please refer to both Installation instructions for fixture and housing.