



SQD35 Deco

Specification Sheet





UL STD 1598 IP67

LUMINAIRE FEATURES

Design and Application

- · Architectural and landscape lighting
- Small interior lobby spaces
- Recessed floor installation
- Gravel, soil or concrete installation
- UL STD 1598, IP67, Wet location, drive over rated 1500 kg (3300lb)

Performance

- · IK10, Tempered glass, crystal clear
- Aluminium construction fixture body
- Stainless steel type 304 flange
- Snap in installation with no exposed hardware
- Galvanic current protection (installation housing)
- Lifetime TM-21@85C L90(9K)=54400h
- Supplied with oil and water resistant 0,3m (1') feed cable as standard
- CRI: > 85
- 2 Step MacAdam

Safety

- Remote power supply
- · Low voltage operation
- Recessed installation

Sustainability

Recyclable material

Installation housing

- SQ35C Concrete
- SQ35T Tiles

Accessories


• 201090 - Removal tool

Power supplies


- List of proposed power supplies that are to be ordered separately.
- Click here for list of available drivers.
- Click <u>here</u> for voltage drop and distances.

FILIX

Trim (TM)



Trimless (TS)



Click $\underline{\text{here}}$ to download fixure installation manual.

Click here to download housing installation manual.

Click here to download CAD file.

Click here to download IES-LTD data.





SQD35 Deco

ORDERING INFORMATION

FSQD35

INSTALATION

TM • Trim (TM)

TS • Trimless (TS)

POWER

L - 1,2W, 2700 - 3000K - 68 lm

• H - 3W, 2700 - 3000K - 186 lm

COLOR TEMP.

• 27 - 2700K

• 30 - 3000K

OPTICS

• SP - Spot - 17°

FL • FL - Flood - 41°

• GR - Graze - 13° x 41°

• SX - Spot - 17° + hex

• FX - Flood - 41° + hex

• GX - Graze - 13x41° + hex

VOLTAGE

• 24 - 24VDC fixture voltage

OPTIONS

• 3 - luminaire supplied with 3m (10') feed cable

• 6 - luminaire supplied with 6m (20') feed cable

9 • 9 - luminaire supplied with 9m (30') feed cable

GLARE CONTROL

• 1 - with half moon







SQD35 Deco


INSTALATION DETAILS


Installation housing - SQ35C - Concrete installation

Installation housing - SQ35T - Tiles installation









Note:

For details on specific depths, tiling thickness and other please refer to both Installation instructions for fixture and housing.